

World's highest field actively shielded split coil magnet for neutron scattering



Raffaele Gilardi

Bruker BioSpin, Industriestrasse 26, 8117 Fällanden ZH, Switzerland

Demand for actively shielded split coil magnets for scattering methods

Requirements for neutron scattering:

- high magnetic fields
- open access (→ split coils)
- no large forces from surrounding materials (→ small stray fields)
- no crosstalk with other instruments (→ small stray fields)
- field sensitive devices (He-3 polarizers, photomultipliers) (→ small stray fields)
- polarized neutrons (→ asymmetric option, small stray fields)




Requirements for synchrotron radiation:

- high magnetic fields
- open access (→ split coils)
- no large forces from surrounding materials (→ small stray fields)
- no crosstalk with accelerator (→ small stray fields)

Split coil magnets for neutron scattering


Field	Location	Comments
≤ 12 T	NIST, LANSCE, ILL, ESRF, JAERI, FRM2, ILL, ISIS, PSI, ...	non-shielded
14.9 T	HMI, ILL, PSI, FRM2	non-shielded (Oxford)
16.0 T	SNS (2009)	actively shielded

Concept of actively shielded split coil magnet




- Field homogeneity:
 - < 5000 ppm in 10 mm DSV (symmetric mode)
 - < 15000 ppm in 10 mm DSV (asymmetric mode)
- Field stability (persistent mode): < 0.02%/hour
- LHe hold time ≥ 1 day at 2.2 K
- LN₂ hold time ≥ 4 days at 4.2 K
- Ramp time to field:
 - ≤ 110 min to 14.5 T at 4.2 K
 - ≤ 240 min from 14.5 T at 4.2 K to 16 T at 2.2 K (including cooling to 2.2 K)
- Maximum admissible cryostat tilt (at 16T) = 2°

Polarized neutrons - asymmetric mode operation



Conclusions / Outlook

- Design review with customers took place in January 2008
- 1. quarter 2008 - 3. quarter 2008: construction of magnet system
- 3. quarter 2008 - 1. quarter 2009: magnet tests at Bruker and at PSI
- 2. quarter 2009: delivery to the Spallation Neutron Source (Oak Ridge, USA)



Acknowledgments



System Development and Production

D. Eckert
C. Beneduce
U. Wagner
P. Mock
J. Hinderer
J. Hunziker



Labor für Neutronenstreuung ETHZ & PSI

Test of material with neutrons

P. Allenspach
M. Zolliker
P. Keller
M. Schneider



Simulations (activation, asymmetric mode operation)

G. Ehlers
L. Santodonato
A. Parizzi
W.T.H. Lee




VTI

E. Lelievre
O. Losserand

Stray fields: shielded vs unshielded magnets

5 Gauss line of unshielded magnet at 16 T



actively shielded
↓
small stray field

5 Gauss line of actively shielded magnet at 16 T